



## General info

### Technical - Spotlights and Tracks

|              |                                         |
|--------------|-----------------------------------------|
| Ean          | 8021696189895                           |
| Item         | SMILE TR 3-PHASE 30W CRI80 36° 4000K BI |
| Installation | Spotlights and Tracks                   |
| Warranty     | 5 years                                 |
| Gross weight | 0.87 kg                                 |
| Volume       | -                                       |

## Technical info

|                          |                                                                                                         |
|--------------------------|---------------------------------------------------------------------------------------------------------|
| Net weight               | 0.87 kg                                                                                                 |
| Insulation class         | II                                                                                                      |
| Protection index         | IP20                                                                                                    |
| Compliance               | CE                                                                                                      |
| Operating temperature    | 0° ~ +40 °C                                                                                             |
| Dimmer                   | Non-dimmable, On-Off                                                                                    |
| Power output             | 220-240 V AC 50/60 Hz                                                                                   |
| Power supply             | In-built, included<br>Replaceable (by qualified operators only),<br>electronic, tridonic                |
| Load resistance          | IK06                                                                                                    |
| Accessories not included | Honeycomb or Elliptical filter, White decorative<br>ring, Single connection on-off, Link on-off profile |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 30 W                                      |
| Emission               | Direct                                    |
| Max consumption        | max 30 W                                  |
| Features LED           | LED COB PHILIPS                           |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 80                                      |
| SDCM                   | 3                                         |
| Light beam             | 36°                                       |
| Light beam flux        | 4200 lm                                   |
| Useful light flux      | 3650 lm                                   |