Rocket

rev. 21-07-2026


General info

Outdoor - Recessed lights



Ean	8021696222837
Item	ROCKET FI D5.5 DOUBLE 4000K
Installation	Recessed lights
Warranty	5 years
Gross weight	0.4 kg
Volume	0.000819 m^3

Technical info



Net weight	0.31 kg
Insulation class	III
Protection index	IP67
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	24 V DC
Power supply	Required, remoted, not included, codes 226187 / 226194 / 226200 / 226217 NO, electronic
Load resistance	IK07
Accessories not included	Remote on-off driver, codes 226187 / 226194 / 226200 / 226217

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	2 W
Emission	Direct
Max consuption	max 2 W
Features LED	LED SMD OSRAM
CCT LED	4000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	-
Light beam flux	160 lm
Useful light flux	15 lm
Photobiological risk	1

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com