
Starlight

rev. 23-07-2026





General info

Outdoor - Spotlights

Ean	8021696248387
Item	STARLIGHT PR 10.0W 3000K
Installation	Spotlights
Warranty	5 years
Gross weight	1.23 kg
Volume	0.001872 m^3

Technical info

Net weight	0.95 kg
Insulation class	III
Protection index	IP67
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	24 V DC
Power supply	Required, remoted, not included NO
Load resistance	IK07
Accessories not included	Glare shielding cover, Ground fixing spike, Remote on-off driver

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	10 W
Emission	Direct
Max consuption	max 10 W
Features LED	LED COB BRIDGELUX
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	30°
Light beam flux	1050 lm
Useful light flux	770 lm
Photobiological risk	1

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com