Ulex

rev. 21-07-2026

General info


Outdoor - Spotlights



Ean	8021696261287
Item	ULEX PR H15 SOURCE
Installation	Spotlights
Warranty	5 years
Gross weight	0.76 kg
Volume	0.002835 m^3

Technical info

Net weight	0.66 kg
Insulation class	I
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Load resistance	IK06
Accessories not included	Glare shielding cover, Base for external connection, Ground fixing spike



Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	8,5 W
Emission	Direct
Max consuption	max 8,5 W
Features LED	LED SMD OSRAM
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	30°
Light beam flux	550 lm
Useful light flux	390 lm

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com