Ulex

rev. 21-07-2026


General info

Outdoor - Spotlights



Ean	8021696261294
Item	ULEX PR H20 SOURCE
Installation	Spotlights
Warranty	5 years
Gross weight	1.36 kg
Volume	0.004 m^3

Technical info



Net weight	1.19 kg
Insulation class	I
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Load resistance	IK06
Accessories not included	Glare shielding cover, Base for external connection, Ground fixing spike

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	15 W
Emission	Direct
Max consuption	max 15 W
Features LED	LED SMD OSRAM
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	30°
Light beam flux	1150 lm
Useful light flux	810 lm

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com