

# Office

rev. 21-07-2026






## General info

### Technical - Systems

| | |
|---|---|
| **Ean** | 8021696271200 |
| **Item** | OFFICE SP ACCENT 4000K NERO |
| **Installation** | Systems |
| **Warranty** | 5 years |
| **Gross weight** | 1.86 kg |
| **Volume** | 0.004128 $m^3$ |

## Technical info

| | |
|---|---|
| **Net weight** | 1.82 kg |
| **Insulation class** | I |
| **Protection index** | IP20 |
| **Compliance** | CE |
| **Operating temperature** | 0° ~ +40 °C |
| **Dimmer** | Non-dimmable, On-Off |
| **Power output** | 220-240 V AC 50/60 Hz |
| **Power supply** | In-built, included<br>Replaceable (by qualified operators only), electronic |
| **Load resistance** | IK06 |

## Source info

| | |
|---|---|
| **Integrated source** | Integrated LED module |
| **Repleaceable source** | Replaceable (by qualified operators only) |
| **Power** | 30 W |
| **Emission** | Direct |
| **Max consuption** | max 30 W |
| **Features LED** | LED SMD |
| **CCT LED** | 4000 K |
| **Duration LED (t. 25°c)** | 50000 h |
| **CRI** | > 90 |
| **SDCM** | 3 |
| **Light beam** | 37° |
| **UGR Maximum** | < 16 |
| **Light beam flux** | 3700 lm |
| **Useful light flux** | 2360 lm |
| **Photobiological risk** | EXEMPT |

**IDEAL LUX s.r.l.**
Via Taglio Destro, 32, 30035 Mirano (Venezia)
**Tel** +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com