

## General info

## Technical - Systems

|              |                             |
|--------------|-----------------------------|
| Ean          | 8021696303796               |
| Item         | EGO WIDE 07W 3000K 1-10V BI |
| Installation | Systems                     |
| Warranty     | 5 years                     |
| Gross weight | 0.29 kg                     |
| Volume       | 0.00124 m <sup>3</sup>      |

## Technical info

|                          |                                       |
|--------------------------|---------------------------------------|
| Net weight               | 0.2 kg                                |
| Insulation class         | III                                   |
| Protection index         | IP20                                  |
| Compliance               | CE                                    |
| Operating temperature    | 0° ~ +40 °C                           |
| Dimmer                   | 1, 1-10V                              |
| Power output             | 48 V DC                               |
| Power supply             | Required, remoted, not included<br>NO |
| Accessories not included | Ego profile                           |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 7 W                                       |
| Emission               | Direct                                    |
| Max consumption        | max 7 W                                   |
| Features LED           | LED SMD SAMSUNG                           |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 110°                                      |
| Light beam flux        | 850 lm                                    |
| Useful light flux      | 640 lm                                    |
| Photobiological risk   | 1                                         |
| Standby power          | < 0.50 W                                  |

