
Gemini

rev. 21-07-2026





General info

Indoor - Suspensions

Ean	8021696304731
Item	GEMINI SP D081 DALI/PUSH OTTONE 3000K
Installation	Suspensions
Warranty	5 years
Gross weight	4.55 kg
Volume	0.07396 m^3

Technical info

Net weight	2.3 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, DALI / Push
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	55 W
Emission	Direct
Max consuption	max 55 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam	130°
Light beam flux	6300 lm
Useful light flux	4300 lm
Photobiological risk	1
Standby power	< 0.50 W

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com