Komodo

rev. 23-07-2026


General info

Indoor - Wall lamps



Ean	8021696306827
Item	KOMODO-2 AP NERO
Installation	Wall lamps
Warranty	5 years
Gross weight	0.8 kg
Volume	0.002079 m^3

Technical info



Net weight	0.7 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	4,5 W
Emission	Direct
Max consuption	max 4,5 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°c)	20000 h
CRI	> 90
SDCM	3
Light beam	25°
Light beam flux	240 lm
Useful light flux	200 lm
Photobiological risk	2
Standby power	< 0.50 W

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com