



## General info

### Technical - Systems

|              |                                     |
|--------------|-------------------------------------|
| Ean          | 8021696321806                       |
| Item         | EGO SPOT DOUBLE 16W 4000K ON-OFF NE |
| Installation | Systems                             |
| Warranty     | 5 years                             |
| Gross weight | 0.37 kg                             |
| Volume       | 0.001716 m <sup>3</sup>             |

## Technical info

|                          |                                                            |
|--------------------------|------------------------------------------------------------|
| Net weight               | 0.27 kg                                                    |
| Insulation class         | III                                                        |
| Protection index         | IP20                                                       |
| Compliance               | CE                                                         |
| Operating temperature    | 0° ~ +40 °C                                                |
| Dimmer                   | Non-dimmable, On-Off                                       |
| Power output             | 48 V DC                                                    |
| Power supply             | Required, remoted, not included<br>NO                      |
| Accessories not included | Narrow or Wide beam optics, Honeycomb filters, Ego profile |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 16 W                                      |
| Emission               | Direct                                    |
| Max consumption        | max 16 W                                  |
| Features LED           | LED COB CITIZEN                           |
| CCT LED                | 4000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 30°                                       |
| Light beam flux        | 2100 lm                                   |
| Useful light flux      | 1580 lm                                   |
| Photobiological risk   | 1                                         |