Squish

rev. 21-07-2026

General info


Indoor - Ceiling lamps



Ean	8021696332406
Item	SQUISH PL D34
Installation	Ceiling lamps
Warranty	5 years
Gross weight	1.6 kg
Volume	0.025092 m^3

Technical info

Net weight	0.76 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	Non-dimmable, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Not required



Source info

Integrated source	Integrated LED module
Repleaceable source	Replaceable (by qualified operators only)
Power	LED 10 W
Emission	Diffuse
Max consuption	max 10 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°c)	25000 h
CRI	> 90
SDCM	3
Light beam	140°
Light beam flux	920 lm
Useful light flux	600 lm
Photobiological risk	EXEMPT
Bulb included	1
Recommended bulb	LED INTEGRATO 920Lm 3000K

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com