


## General info

## Technical - Systems



|              |                           |
|--------------|---------------------------|
| Ean          | 8021696332765             |
| Item         | DEVA SPOT 2,5W 3000K NERO |
| Installation | Systems                   |
| Warranty     | 5 years                   |
| Gross weight | 0.04 kg                   |
| Volume       | 0.001089 m <sup>3</sup>   |

## Technical info

|                          |                                       |
|--------------------------|---------------------------------------|
| Net weight               | 0.03 kg                               |
| Insulation class         | III                                   |
| Protection index         | IP20                                  |
| Compliance               | CE                                    |
| Operating temperature    | 0° ~ +40 °C [DO NOT COVER]            |
| Dimmer                   | Non-dimmable, On-Off                  |
| Power output             | 24 V DC                               |
| Power supply             | Required, remoted, not included<br>NO |
| Accessories not included | Deva profile, Narrow beam optic       |

## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | 2,5 W                                     |
| Emission               | Direct                                    |
| Max consumption        | max 2,5 W                                 |
| Features LED           | LED SMD                                   |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 30000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam             | 37°                                       |
| Light beam flux        | 150 lm                                    |
| Useful light flux      | 110 lm                                    |
| Photobiological risk   | 2                                         |