

## General info

## Indoor - Wall lamps



|              |                        |
|--------------|------------------------|
| Ean          | 8021696345499          |
| Item         | BONNE NUIT-2 AP BIANCO |
| Installation | Wall lamps             |
| Warranty     | 5 years                |
| Gross weight | 0.46 kg                |
| Volume       | 0.00168 m³             |

## Technical info

|                       |                                                                                |
|-----------------------|--------------------------------------------------------------------------------|
| Net weight            | 0.36 kg                                                                        |
| Insulation class      | II                                                                             |
| Protection index      | IP20                                                                           |
| Compliance            | CE                                                                             |
| Operating temperature | 0° ~ +40 °C                                                                    |
| Dimmer                | Non-dimmable, On-Off                                                           |
| Power output          | 220-240 V AC 50/60 Hz                                                          |
| Power supply          | In-built, included<br>Replaceable (by qualified operators only),<br>electronic |



## Source info

|                        |                                           |
|------------------------|-------------------------------------------|
| Integrated source      | Integrated LED module                     |
| Replaceable source     | Replaceable (by qualified operators only) |
| Power                  | LED 6,5 W                                 |
| Emission               | Direct                                    |
| Max consupction        | max 6,5 W                                 |
| Features LED           | LED SMD CREE                              |
| CCT LED                | 3000 K                                    |
| Duration LED (t. 25°C) | 50000 h                                   |
| CRI                    | > 90                                      |
| SDCM                   | 3                                         |
| Light beam flux        | 420 lm                                    |
| Useful light flux      | 340 lm                                    |
| Photobiological risk   | 2                                         |
| Bulb included          | 1                                         |
| Recommended bulb       | LED INTEGRATO 420Lm 3000K                 |