Dorica

rev. 21-07-2026





General info

Indoor - Floor lamps

Ean	8021696354668
Item	DORICA PT1 ARANCIONE
Installation	Floor lamps
Warranty	5 years
Gross weight	6.4 kg
Volume	-

Technical info

Net weight	5 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	1, Dimmer on board
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable, electronic

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	LED 50 W
Emission	Direct
Max consuption	max 50 W
Features LED	LED SMD BRIDGELUX
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
SDCM	3
Light beam flux	6000 lm
Useful light flux	2590 lm
Photobiological risk	1
Standby power	< 0.50 W
Bulb included	1
Recommended bulb	LED INTEGRATO 6000Lm 3000K

IDEAL LUX s.r.l.
Via Taglio Destro, 32, 30035 Mirano (Venezia)
Tel +39 041 5790500 | **Fax** +39 041 8872349 | **E-mail** info@ideal-lux.com
www.ideal-lux.com